



The classic 261 is one of the most popular Impactools™ in its class. It provides plenty of power and rugged durability in a convenient easy-to-use package.

- 1 491 Nm (1 100 ft-lb) of maximum torque in reverse.
- The Ingersoll Rand impact mechanism with proprietary advanced metallurgy provides the ultimate in durability and reliability.
- Pressure-feed lubrication system automatically greases the impact mechanism for increased durability and reliability.
- Steel hammercase provides superior durability under the toughest use.
- Powerful 6-vane motor delivers superior performance.
- Feather-touch trigger allows precise delivery of power and speed.
- Wide range of power regulator settings helps adjusting the power to the application.
- Through-handle exhaust directs air away from the operator.

Specifications at 6,2 bar (90 psi)

| | |
|---|----------|
| Part Number | 261 |
| Ordering number | 01209758 |
| Drive size (square) | 3/4 in |
| Other available versions: | |
| - 3/4" square drive, 75 mm (3") extended anvil | 261-3 |
| - 3/4" square drive, 150 mm (6") extended anvil | 261-6 |
| - 1" square drive, standard length anvil | 271 |

PERFORMANCE

| | |
|---------------------------|--------------------------------|
| Working torque in forward | 200 - 600 ft-lb / 271 - 813 Nm |
| Maximum torque in forward | 1 100 ft-lb / 1 491 Nm |
| Working torque in reverse | 200 - 600 ft-lb / 271 - 813 Nm |
| Maximum torque in reverse | 1 100 ft-lb / 1 491 Nm |
| Free speed | 5 500 rpm |
| Impacts per minute | 1 000 |

AIR SYSTEM

| | |
|-------------------------|----------------------|
| Air Inlet (NPTF) | 3/8 in |
| Minimum hose size | 1/2 in / 13 mm |
| Average air consumption | 9,5 CFM / 269 L/min |
| Air consumption at load | 38 CFM / 1 076 L/min |

NOISE & VIBRATION

| | |
|--|-----------------------------|
| Sound pressure / power (ISO15744) | 98,1 / 109,1 dB(A) |
| Vibration level / measurement uncertainty (ISO28927) | 10,4 / 1,3 m/s ² |

WEIGHT & DIMENSIONS

| | |
|---------------------------------|--------------------|
| Tool weight | 12,4 lb / 5,62 kg |
| Tool length | 8,8 in / 224 mm |
| Shipping weight | 14,2 lb / 6,45 kg |
| Shipping dimensions (L x W x H) | 284 x 315 x 117 mm |
| UPC / EAN code | 6 63023 00104 3 |
| Origin | Made in China |




SK6M6L

81287401

3/4" Impact socket set (6 pcs) (24, 27, 30, 32, 33 and 36 mm)


E6175MM

81286130

3/4" Extension 175 mm


E6100MM

81286122

3/4" Extension 100 mm


Impact sockets

For the complete range, see our accessory catalogue.


2920A90, 2920B-A827

03797669, 03797651

3/4" right-angle head


910-366

03403896

Horizontal hanger


BMDLN-8

17023755

Cable balancer, 6-8 kg, 2,5 m (8-1/4 ft)


261-BOOT

45505468

Protective tool boot


IB6NMC3

88103023

IBN/IBS Series nipple, 3/8" male thread, 6 mm bore (ISO6150B / MIL-C4109)


IB8NMC3

88103304

IBN/IBS Series nipple, 3/8" male thread, 8 mm bore (ISO6150B / MIL-C4109)


77NMC3

88104088

7N7/7S7 Series nipple, 3/8" male thread, 7,2 mm bore (EURO 7,2 - 7,4)


Quick Release Couplings

For the complete range, see our accessory catalogue.


Filters, regulators, lubricators

For the complete range, see our accessory catalogue.


105-LBK1

04616090

Lubricant kit for Impacttools™ with metal housing


10Z4

03875671

Oil, Class 1, no. 10, 0,12 L


105-4T-6

04618930

Grease for Impacttools hammer mechanism (6 tubes)


Lubricants

For the complete range, see our accessory catalogue.


261-THK1

22039259

Impact mechanism service kit


261-TK2

03866597

Motor service kit

www.ingersollrandproducts.com

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.

© 2008 Ingersoll-Rand Company — Form No. PDS_261_EN_02/03/2011