

MX Series

- ▶ No costly side rods and springs
- ▶ Composite valve eliminates rusting
- ▶ Directional exhaust eliminates blow back
- ▶ Built in lubricator
- ▶ Hand serviceable shank doesn't require a press to service
- ▶ Backhead conforms to operators leg
- ▶ Optional muffler sold separately



MX60A



MX90

MX Series with IR Flex-Handle™

- ▶ IR Flex-Handles provide vibration dampening in a full 360 degree range of movement. Competitive mechanical springs only work in one direction and lose their ability to absorb vibration when fully compressed, or when hammering while pulling the breaker out of the work surface.



MX60AF



MX90AF

MODEL	Hex Shank Size	Stroke in (mm)	Bore in (mm)	Length w/o Accessory in (mm)	Weight w/o Accessory lb (kg)	bpm	cfm	Inlet Size in NPT	Recomm. Hose Size in (mm)	Muffler Part Number
STANDARD MODELS										
MX60A	1-1/8" x 6"	5.75" (146)	2.06" (52.3)	27.5" (686)	76 (31.8)	1250	70	3/4"	3/4" (19)	04704862
MX60B	1-1/4" x 6"	5.75" (146)	2.06" (52.3)	27.5" (686)	76 (31.8)	1250	70	3/4"	3/4" (19)	04704862
MX90A	1-1/8" x 6"	5.75" (146)	2.62" (66.5)	27.5" (686)	87 (39.5)	1250	85	3/4"	3/4" (19)	04704862
MX90B	1-1/4" x 6"	5.75" (146)	2.62" (66.5)	27.5" (686)	87 (39.5)	1250	85	3/4"	3/4" (19)	04704862
VIBRATION REDUCED FLEX-HANDLE MODELS										
MX60AF	1-1/8" x 6"	5.75" (146)	2.06" (52.3)	27.5" (686)	76 (31.8)	1250	70	3/4"	3/4" (19)	04704862
MX60BF	1-1/4" x 6"	5.75" (146)	2.06" (52.3)	27.5" (686)	76 (31.8)	1250	70	3/4"	3/4" (19)	04704862
MX90AF	1-1/8" x 6"	5.75" (146)	2.62" (66.5)	27.5" (686)	87 (39.5)	1250	85	3/4"	3/4" (19)	04704862
MX90BF	1-1/4" x 6"	5.75" (146)	2.62" (66.5)	27.5" (686)	87 (39.5)	1250	85	3/4"	3/4" (19)	04704862

Performance figures are at 90 psi (6.2 bar) air pressure.